Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1   1.   (Currently amended): An external storage ~~subsystem~~system comprising:

2   a plurality of disk drives for storing data;

3   a drive interface control unit operatively couple to the disk drives;

4   a channel interface control unit through which a connection with a supervisory

5   unit can be established for reading and writing data;

6   a cache memory connected to the drive interface control unit and to the channel

7   interface control unit, the cache memory for temporarily storing data between the disk interface

8   control unit and the channel interface control unit; and

9   a shared memory connected to the drive interface control unit and to the channel

10   interface control unit, the shared memory for storing information relating to data that is to be

11   staged to the cache memory,

12   the information being used by the channel interface control unit to stage data that

13   is stored in a plurality of tracks in one or more of the disk drives to the cache memory by way of

14   the drive interface control unit,

15   the information further being used by the channel interface control unit to destage

16   data from the cache memory to be stored to the disk drives by way of the drive interface control

17   unit,

18   wherein staging of the data to the cache memory and destaging of the data from

19   the cache memory are performed according to staging and destaging instructions from the

20   supervisory unit, the instructions formulated by the supervisory unit according to criteria

21   provided by a user.

Appl. No. 09/591,104
Amdt. sent October 19, 2004
Reply to Office Action of July 6, 2004

PATENT

1   2.   (Currently amended) An external storage ~~subsystem~~system having at

2   ~~lease~~ least one disk drive and having a cache memory to store data that is read from the disk

3   drive and to store data to be written to the disk drive, collectively referred to as user data,

4   wherein the user data on the at least one disk drive is stored to the cache memory in response to a

5   first instruction from the host computer, ~~or~~ and wherein the user data is removed from the cache

6   memory and stored to the at least one disk drive in response to a second instruction from the host

7   computer ~~based on user defined information and upon operating information provided to the~~

8   ~~external storage subsystem~~.

1   3.   (Currently amended): The external storage ~~subsystem~~system as claimed

2   in claim 1, in which the staging in or destaging from the cache memory of the user data is

3   executed in a processing unit of a data-set domain.

1   4.   (Currently amended): The external storage ~~subsystem~~system as claimed

2   in claim 2, in which the storage in or removal from the cache memory of the user data is

3   executed in a processing unit of data-set domain.

1   5.   (Currently amended): An information processing system having an

2   external storage ~~subsystem~~system and a host unit which is external to the external storage

3   ~~subsystem~~system and connected to the external storage ~~subsystem~~system, in which the external

4   storage ~~subsystem~~system comprises a plurality of disk drives, a drive interface control unit, a

5   channel interface control unit, a shared memory, and a cache memory, in which the host unit

6   executes writing and reading data to the external storage ~~subsystem~~system, and in which

7   the host unit has a host utility program to manage data in the cache memory, and

8   user defined information or operating information of the external storage ~~subsystem~~system for

9   execution of the host utility program,

10   wherein the host utility program can issue a resident command to instruct the

11   channel interface control unit to set residing data in the cache memory, and can issue a reset

12   command to instruct the channel interface control unit to reset residing data in the cache

13   memory,

14   wherein the channel interface unit in the external storage ~~subsystem~~system

15   receives the resident command and the reset command based on the user defined information or

16   the operating information,

17   wherein the drive interface control unit is operable to store data on the disk drives,

18   wherein the cache memory is in data communication with the drive interface

19   control unit and the channel interface control unit,

20   wherein the shared memory is in data communication with the drive interface

21   control unit and the channel interface control unit, and stores first information relating to data

22   stored in the cache memory,

23   wherein the channel interface control unit sets and resets residing data in the

24   cache based on the first information.

1   6.   (Original): The information processing system as claimed in claim 4, in

2   which the storage of a set of user data in the cache memory or removal of the user data from the

3   cache memory is executed in a unit of data-set domain.

1   7.   (Currently amended): The information processing system as claimed in

2   claim 4, in which the user defined information includes a data-set name which is entered from a

3   terminal connected to the host ~~unit~~computer.

1   8.   (Original): The information processing system as claimed in claim 5, in

2   which the user defined information includes a data-set name which is entered from a terminal

3   connected to the host unit.

1   9.   (Previously presented): A system comprising a host unit and a disk array

2   system separate from the host unit and in data communication therewith, the disk array system

3   comprising:

4   a plurality of disk drives for storing data;

5   a drive interface control unit operably coupled to the disk drives for transfer of

6   data therewith;

7   a channel interface control unit to receive data transfer commands from a host

8   unit;

9   a cache memory in data communication with channel interface control unit and

10 with the drive interface control unit; and

11   a shared memory in data communication with channel interface control unit and

12 with the drive interface control unit, the shared memory having stored therein first information

13 relating to data staged in the cache,

14   wherein the host unit can issue a resident command and a reset command;

15   wherein in response to receiving a resident command from the host unit, the

16 channel interface control unit accesses the first information to store data received from disk

17 drives into the cache memory,

18   wherein in response to receiving a reset command from the host unit, the channel

19 interface control unit accesses the first information to reset data that is stored in the cache

20 memory.